






## Sundream Pergola Awning Comparison Table

	<b>Sundream®</b>  Conservatory	<b>MaxiRail</b>  Integrated Frame	<b>Compact</b>  Compact Design	<b>ZipFast®</b>  Zip Fabric	<b>Cubix™</b>  Teleskopik Parts
<b>Key dimensions (mm)</b>					
Headbox size (h x d)	170 x 230	171 x 231	145 x 163	145 x 163	145 x 166
Fixing height (incl. mounting)	213	Posts	158	169	184
Guiderail dimensions (h x d)	65 x 52	95 x 60	52 x 30	68 x 55	68 x 55
Front rail dimensions (h x d)	68 x 120	68 x 120	52 x 80	52 x 80	52 x 80
Post dimension (Int / Ext)	-	60 x 60	-	-	70 / 86
Distance guiderail to fabric	30	20	25	0	0
Distance front extrusion to end	70	75	0	0	0
<b>Width / Projection (mm) / Area (m²)</b>					
Width range (single unit)	1350 - 6500	1450 - 6500	1400 - 6000	1400 - 5000	1400 - 6000
Maximum projection	6500	6500	5000	5000	5000
Maximum cantilever	1500	2500	300	500	500
Maximum area (single unit)	39	35	20	20	20
<b>Wind class (km/hr)</b>					
Wind rating	38	38	38	49	49
<b>Installation features</b>					
Coupled (multiple units)	A (max. 4)	-	-	-	-
Dual mount (multiple units)	A	A	A	A	A
<b>Steer-Around</b>	A	-	-	-	-
Integrated frame / posts	-	✓	-	-	-
<b>Teleskopik</b> front post	-	-	-	-	A
Lateral adjusting mount brackets	✓	Posts	-	-	-
Extension / Side mount brackets	A	Posts	A	A	A
Fabric support extrusion (by size)	✓	✓	-	-	✓
<b>Operation / Automation (only)</b>					
Motorised hardwired / remote	✓/A	✓/A	✓/A	✓/A	✓/A
Wind and rain sensors	A	A	A	A	A
<b>Fabric</b>					
Acrylic / PVC mesh (size limits)	✓/A	✓/A	✓/A	✓/A	✓/A
Fabric	-	-	-	✓	✓
<b>Powdercoat</b>					
Dulux Duralloy / Interpon Base	✓	✓	✓	✓	✓
Dulux / Interpon / Other finishes	A	A	A	A	A
<b>Warranty</b>					
Warranty years (conditions apply)	5	5	5	5	5

✓ Standard feature      A Available feature      - Not available or not applicable  
*Designs and specifications for all awnings are subject to change without notice*

